

# Non-Reactive Standard

Milliken

## ADHESIVE

For Carpet : Non-reactive adhesive for most applications (exception: extreme moisture)



NO LIMIT



NO LIMIT  
New Construction



UP TO 95%  
Renovations



DRY TIME  
10-20 min



WORKING TIME  
indefinite



4-Gallon Pail  
Trowel / Roll-on

## Non-Reactive Pressure Sensitive Adhesive

### NEW CONSTRUCTION

For use with  
RH up to:

**No Limit**

Installation  
after new pour:

**60 days**

No testing required. No pH/RH limit.

### RENOVATION

Above-grade  
RH up to:

**No Limit**

On-grade, RH with  
no vapor retarder:

**95%**

On-grade with vapor retarder: No limit.



The Benefits of  
Milliken Adhesives

Milliken offers adhesive solutions for any scenario:

- Modular carpet, LVT, mixed-media
- Normal RH and pH
- Extreme RH and no-testing solutions
- Trowel-on and Spray options for most applications
- No primers, no sealants, limited floor prep required



1/16" x 1/32"  
x 1/32"  
U-Notch

### FLOORING TYPE

Modular Carpet Tile

### ESTIMATED COVERAGE

180-225 sf/gal



3/4"-1"  
Nap Paint  
Roller

### FLOORING TYPE

Modular Carpet Tile

### ESTIMATED COVERAGE

Up to 350 sf/gal

# Non-Reactive Standard Adhesive



PRODUCT CHARACTERISTICS	Product Classification	Roll or trowel pressure sensitive adhesive
	Base Chemistry	Acrylic emulsion
	Appearance	Mint green to green tint as adhesive dries
	Consistency	Thin syrup
	Application	Trowel or roller
	Flammability	Non-flammable
	Freeze/Thaw	Protect from freezing
	Shelf Life	2 years (unopened)
MOISTURE	RH	New Construction - No Limit, No testing if installed 60 days after a new pour.
		Renovation (above-grade) - No Limit, No testing
		Renovation (on-grade with a confirmed vapor barrier) - No Limit
		Renovation (on-grade) - 95%
	pH	No limit
TIME/TRAFFIC	Open Time	Indefinite
	Dry Time	10-20 mins
	Working Time	Indefinite
	Traffic	Immediately
SUSTAINABILITY	Solvents	None
	Certifications	CRI Green Label Plus

**STORAGE** This product should be stored at temperatures between 40-100°F (4-38° C). While this product is freeze-thaw stable, it is necessary to protect it from freezing.

**CAUTION** DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

**WARRANTY** For Milliken installation instructions and warranties, visit [millikenfloors.com](http://millikenfloors.com).



Customer Concierge 800.824.2246 | [millikenfloors.com](http://millikenfloors.com)

©2022 Milliken & Company | Design ©Milliken & Company | Made in the USA