

# LVT Moisture XT with Acousti-Loc Technology



ADHESIVE

For LVT

2 mm, 2.5 mm & 5 mm FlexForm™ LVT



NO LIMIT



NO LIMIT



DRY TIME  
10 min (wet set)



WORKING TIME  
45 min



ROLL FLOOR  
within 1 hr



CURE TIME  
6 hrs



LIGHT TRAFFIC  
3 hrs



HEAVY TRAFFIC  
4 hrs



HEAVY ROLLING  
LOADS : 8 hrs



2-Gallon Pail  
Trowel

## Unlimited Moisture Vapor Barrier Adhesive

For use with RH up to

**No RH Limit**

No pH or RH limits.  
NO TESTING REQUIRED.

Installation after new pour:

**45 days**



The Benefits of  
Milliken Adhesives

Milliken offers adhesive solutions for any scenario:

- Modular carpet, LVT, mixed-media
- Normal RH and pH
- Extreme RH and no-testing solutions
- Trowel-on and Spray options for most applications
- No primers, no sealants, limited floor prep required

1/16" x 1/32"  
x 1/32"

U-Notch

FLOORING TYPE

2 mm, 2.5 mm & 5 mm  
FlexForm™ LVT

ESTIMATED COVERAGE

165 - 220 sf/gal



CONTRIBUTES TO  
**HIGHER IIC**  
RATING

Acousti-Loc Technology  
provides measurable  
acoustic benefits

# LVT Moisture XT with Acousti-Loc Technology



PRODUCT CHARACTERISTICS	Product Classification	Modified urethane (isocyanate free)
	Base Chemistry	STPE polymer-based (Hybrid Propel®)
	Curing Method	Moisture cure
	Appearance	Off white
	Consistency	Smooth, low viscosity liquid
	Application	Easy troweling
	Flammability	Non-flammable
	Freeze/Thaw	Stable to 10°F (-12°C)
	Shelf Life	1 year
MOISTURE	Moisture Control	Protects flooring against unlimited moisture
	RH [ASTM F2170]	No testing required (100%)
	pH	No testing required (5-14)
	MVER [ASTM F1869]	No testing required
TIME	Open Time	10 min
	Dry Time	10 min (flash time)
	Working Time	45 mins
	Roll & Cross Roll Floor (75- 100lb roller)	Between 1 - 2 hours after installation (use hand roller during install)
	Cure Time	6 hours
TRAFFIC	Light Traffic	3 hrs
	Heavy Traffic	4 hrs
	Heavy Rolling Loads	8 hrs
SUSTAINABILITY	Solvents	None
	Isocyanates	None
	Total VOCs	0.5 mg/m <sup>3</sup> or less
	Compliant with	California DPH Section 01350 Version 1.2
	Certifications	CRI Green Label Plus
ACOUSTICS	IIC	Increased IIC ratings dependent upon your ceilings and subfloor construction

**STORAGE** This product should be stored at temperatures between 50-90°F (15-32° C). While this product is freeze-thaw stable, it is necessary to protect it from freezing. Freeze/thaw stable to 10°F (-12°C).

**CAUTION** DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

**WARRANTY** For Milliken installation instructions and warranties, visit [millikenfloors.com](http://millikenfloors.com).



Customer Concierge 800.824.2246 | [millikenfloors.com](http://millikenfloors.com)

©2022 Milliken & Company | Design ©Milliken & Company | Made in the USA