

Mosaic 95

Milliken

ADHESIVE

For Mixed Media

Carpet Tile | 5 mm FLEXFORM™ LVT



pH

UP TO 11

RH

UP TO 95%



DRY TIME
30+ min



WORKING TIME
8 hrs



LIGHT TRAFFIC
24 hrs



HEAVY TRAFFIC
72 hrs



4-Gallon Pail
Trowel / Roll-on

Aggressive-Tack Mixed-Media Adhesive

For use with RH up to **95%**

Milliken is also the only manufacturer to offer adhesives with **no pH or RH limits** and which **require no testing**. Talk to your sales rep to learn more.

Installation after new pour: **45 days**



The Benefits of
Milliken Adhesives

Milliken offers adhesive solutions for any scenario:

- Modular carpet, LVT, mixed-media
- Normal RH and pH
- Extreme RH and no-testing solutions
- Trowel-on and Spray options for most applications
- No primers, no sealants, limited floor prep required



1/32" x 1/16"
x 1/32"

U-Notch

FLOORING TYPE

Carpet Tile/
5 mm FLEXFORM LVT

ESTIMATED COVERAGE
185-245 sf/gal



3/8"
Short Nap
Paint Roller

FLOORING TYPE

Carpet Tile/
5 mm FLEXFORM LVT

ESTIMATED COVERAGE
200 - 260 sf/gal

PRODUCT CHARACTERISTICS	Product Classification	Pressure sensitive adhesive
	Base Chemistry	Acrylic polymer
	Solids Content	40% to 60%
	Density	8.3 lbs. per U.S. gal. (1.0 g per mL)
	Appearance	Light tan
	Application	Trowel or roller
	Flash Point	> 212°F (100°C)
	Shelf Life	2 years (unopened)
MOISTURE	RH	95%
	pH	Up to 11
TIME	Flash Time (permanent bond)	0 min
	Flash Time (pressure-sensitive)	30 min or until dry
	Working Time	15 mins (permanent bond), 8 hrs (PSA)
TRAFFIC	Light Traffic	12 hrs
	Heavy Traffic	72 hrs
SUSTAINABILITY	VOC (g/L) - SCAQMD Rule#1168	<40
	LEED Points	Health product declaration — up to 2 points
	Certifications	CRI Green Label Plus, LBC Red List Free

STORAGE This product should be stored at temperatures between 40-100°F (4-38° C). While this product is freeze-thaw stable, it is necessary to protect it from freezing.

CAUTION DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

WARRANTY For Milliken installation instructions and warranties, visit millikenfloors.com.